

Kinetic Polymers

D-13/2, Phase – 1, Road No : 3,IDA,Jeedimetla,Hyderabad – 500 055.
Phone No : 040 – 65278344 , 65408277 , Tele Fax No : 040 – 23093957
E-Mail : kineticpolymers@gmail.com , Web site : www.kineticpolymers.com

ANTISTATIC FLOOR CLEANING SOLUTION CONCENTRATED

Antistatic Flooring and Table Top attracts dust and contamination. Can be the Cause for ESD failure.

Antistatic solution, when applied would create a conductive path on that inaccessible surface discharging the static charges temporarily affecting for approximately 48 hours depending on the usage. This solution has got a detergent action also so that the surface gets clean apart from improving the antistatic properties.

DILUTE THIS SOLUTION WITH WATER IN RATIO OF 1: 20

(1 LITER SOLN: 20 LITER WATER.) AND THEN USE IT

Note : Validity period will be Six Months

Specifications :

- **For clean room of class 10 , class 100 & class 10000**
- **Low Potassium content (In ppb)**
- **Low Ionic, no foam formulation**
- **No static charge generation**
- **Particle free solutions, filter to 0.1 microns**
- **Soluble in DI Water & Distil water**

Kinetic Polymers

D-13/2, Phase – 1, Road No : 3,IDA,Jeedimetla,Hyderabad – 500 055.
Phone No : 040 – 65278344 , 65408277 , Tele Fax No : 040 – 23093957
E-Mail : kineticpolymers@gmail.com , Web site : www.kineticpolymers.com

ANTISTATIC FLOORING

Do's

- 1) Always clean the floor with antistatic floor cleaning solutions.
- 2) Only mopping is necessary.
- 3) Regular check the antistatic values of the flooring using SRM meter with probes.

Don't

- 1) Use Ordinary Water / Soap water / Mild acid / liquid soap to clean the floor.
- 2) Pour the solution on the floor at once as it will be difficult to clean.
- 3) Use of heavy metal trolleys with metal wheels, it will damage the flooring.